


Global Trac Electrical Accessories

GLOBAL TRAC PULSE X FEED BLACK

XTSC638-2



Product features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate X-feed that is applicable for three-circuit track systems where the polarity ridge is in the outer side and on the left. Dimensions - 166 x 166 x 33 mm (L x W x H), black (RAL 9005).



PRODUCT OVERVIEW

Product name	GLOBAL TRAC PULSE X FEED BLACK
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
ETIM Class	EC002556
Warranty	5 years
Light colour	N/A
Dimmable	Yes
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532659

DATA TABLE

General data

Product name	GLOBAL TRAC PULSE X FEED BLACK
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
Operating temperature range (°C)	0°C - 25°C
ETIM Class	EC002556
Warranty	5 years

Optical data

Light colour	N/A
--------------	-----

Electrical data

Mains voltage (V)	220-240V~
Dimmable	Yes

Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	166

Global Trac Electrical Accessories

GLOBAL TRAC PULSE X FEED BLACK
XTSC638-2

Nominal Product Width (mm)	166
Nominal Product Height (mm)	33
Weight (kg)	0.32

Packaging

Single packaging type	Plastic
Product EAN number	6410014532659
Packaging single length / height (cm)	30.0
Packaging single width (cm)	30.0
Packaging single depth (cm)	0.32
DUN14 (outer)	06410014532659
Units per outer package	10
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	25.0

Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes