

## Start Tubular - Electronic

Start Tubular IP66 114 EB 840  
0042300



### Product features

- 



## PRODUCT OVERVIEW

Product name	Start Tubular IP66 114 EB 840
Technology	Fluorescent
Cap/Base	G5
Housing	PC Polycarbonate
Environment	Interior
General application	Hospitality, Logistics & Industry
ETIM Class	EC000109
Warranty	2 years
Fixture luminous flux (lm)	1140
Luminaire efficacy (lm/W)	76
LOR (%)	80
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	85
Total power consumption (W)	15
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP66
IK rating	IK08
Product EAN number	5410288423005
Light source included	0002761

## PHOTOMETRY


## Start Tubular - Electronic

Start Tubular IP66 114 EB 840  
0042300

Distance [m]	Cone diameter [m]	E07	E180	E270	Illuminance [lx]
0.5	1.40 4.56	54.4°	78.8°	91.7°	91
1.0	2.79 9.92	54.4°	78.8°	91.7°	22.8
1.5	4.19 14.88	54.4°	78.8°	91.7°	10.2
2.0	5.59 19.84	54.4°	78.8°	91.7°	5.7
2.5	6.98 24.80	54.4°	78.8°	91.7°	4.1
3.0	8.38 29.76	54.4°	78.8°	91.7°	3.1

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 18.8°)  
— C90 - C270 (Half beam angle: 108.8°)



## TECHNICAL DRAWINGS

