

Global Trac Electrical Accessories

GLOBAL TRAC PULSE T OUT-RIGHT BLACK

XTSC636-2



Product features

- Global Trac Pulse accessory - Glass fiber reinforced polycarbonate T-feed that is applicable for three-circuit track systems where the polarity ridge is in the outer side and on the right. Dimensions - 166 x 99 x 33 mm (L x W x H), black (RAL 9005).



PRODUCT OVERVIEW

Product name	GLOBAL TRAC PULSE T OUT-RIGHT BLACK
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
ETIM Class	EC002556
Warranty	5 years
Light colour	N/A
Dimmable	Yes
Housing colour	RAL 9005 - Jet black
IP rating	IP20
IK rating	IK02
Product EAN number	6410014532574

DATA TABLE

General data

Product name	GLOBAL TRAC PULSE T OUT-RIGHT BLACK
Technology	Accessory
Housing	PC Polycarbonate
General application	Retail
Operating temperature range (°C)	0°C - 25°C
ETIM Class	EC002556
Warranty	5 years

Optical data

Light colour	N/A
--------------	-----

Electrical data

Mains voltage (V)	220-240V~
Dimmable	Yes

Physical data

Housing colour	RAL 9005 - Jet black
IP rating	IP20

Global Trac Electrical Accessories

GLOBAL TRAC PULSE T OUT-RIGHT BLACK
XTSC636-2

IK rating	IK02
Nominal Product Length (mm)	166
Nominal Product Width (mm)	99
Nominal Product Height (mm)	33
Weight (kg)	0.2

Packaging

Single packaging type	Plastic
Product EAN number	6410014532574
Packaging single length / height (cm)	30.0
Packaging single width (cm)	16.7
Packaging single depth (cm)	0.32
DUN14 (outer)	06410014532574
Units per outer package	20
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	25.0

Safety data

Optimal operating condition (°C)	0-25
Special purpose lamp	No
Dry applications use only	Yes