

Aquastar T8

F25W/30Aquastar Retail
0000645



Product features

- Colour temperature 10,000K recreating the tropical light spectrum. For fresh and marine aquariums. Excellent combination with DaylighStar. Outstanding results in combination with Daylightstar.



PRODUCT OVERVIEW

Product name	F25W/30Aquastar Retail
Technology	Fluorescent
Lamp shape	Tubular shape
Type	T8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	SPG
ETIM Class	EC000108
Luminous flux (lm)	1500
Colour temperature (K)	10000
Light colour	Aquastar
Wattage (W)	25.00
Product Voltage (V)	84
Dimmable	Yes
Average life (Nominal) (h)	10000
Product EAN number	5410288006451

DATA TABLE

General data

Product name	F25W/30Aquastar Retail
Technology	Fluorescent
Lamp shape	Tubular shape
Type	T8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Open
General application	SPG
Operating temperature range (°C)	-15°C - 40°C
ETIM Class	EC000108

Optical data

Aquastar T8

F25W/30Aquastar Retail
0000645

Luminous flux (lm)	1500
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	10000
Light colour	Aquastar
Adjustable chromaticity	N

Electrical data

Wattage (W)	25.00
Watt (Rated) - High frequency (W)	24.50
Current (A)	0.360
Product Voltage (V)	84
Control gear required	Yes
Transformer required	No
Dimmable	Yes
Drive current (mA)	360

Lifetime data

Average life (Nominal) (h)	10000
Average life (Rated) (h)	10000

Physical data

Nominal Product Length (mm)	750.0
Nominal Product Diameter (mm)	26
Max. Length base to base (mm) - A	742.2
Length base to pin Min-Max (mm) - B	746.9-749.3
Max. Lamp Length (mm) - C/L	756.4
Max. Lamp Diameter (mm) - D	28.0
Weight (kg)	0.102

Packaging

Single packaging type	Carton
Product EAN number	5410288006451
Packaging single length / height (cm)	82.5
Packaging single width (cm)	2.7
Packaging single depth (cm)	2.7
DUN14 (outer)	15410288006458
Units per outer package	10
Packaging outer length / height (cm)	85.5
Packaging outer width (cm)	6.5
Packaging outer depth (cm)	14.7

Safety data

Lamp mercury content (mg)	2.80
Optimal operating condition (°C)	-15-40
Breakage cleaning instructions	Applicable
Special purpose lamp	Yes
Intended purpose	Petcare (not including High UV content)
Suitable for household illumination	No

Aquastar T8
F25W/30Aquastar Retail
0000645

Safety message

Not suitable for household

TECHNICAL DRAWINGS

