

Flex Pro Medium Output


Flex Pro IP65 4400lm 930

0068180



Product features

- 5 metre IP65 LED reel with pre-attached 3M adhesive type; equipped with 600 LEDs; 4400lm per 5m (880lm per 1m); 24V; 3000K; CRI90; R9>50; SDCM 3




PRODUCT OVERVIEW

Product name	Flex Pro IP65 4400lm 930
Technology	LED
Housing	Other
General application	Hospitality
ETIM Class	EC002706
E-number FI	4278335
Warranty	5 years
Fixture luminous flux (lm)	4400
Luminaire efficacy (lm/W)	92
Colour temperature (K)	3000
CRI (Ra)	90
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Photobiological Risk Group	RG1
Total power consumption (W)	48
Electrical protection	Class III
Dimmable	Yes
Housing colour	Transparent
IP rating	IP65
IK rating	IK00
Product EAN number	5410288681801


PHOTOMETRY

Distance [m]	Cone diameter [m]	Illuminance [lx]
0.5	1.46	1233
1.0	2.91	308
1.5	4.37	131
2.0	5.82	71
2.5	7.28	49
3.0	8.73	34

— C0 - C180 (Half beam angle: 111.0°)
 — C90 - C270 (Half beam angle: 111.0°)



Flex Pro Medium Output Flex Pro IP65 4400lm 930 0068180



TECHNICAL DRAWINGS

