

Inverto Pendant

Inverto Pendant NW Eb White
3070050



Product features

- Surface mounted Pendant, wire to base with pluggable connection for easy installation, suitable for looping, switchable driver, white coloured aluminium housing, 1,617lm or 2,045lm, 16W or 19W, 102lm/W or 107lm/W, 4000K, 350mA or 450mA, CRI:80, 40° beam Angle, non-dimmable, IP20, IK07, 50,000hrs (L70), 18.50x24.5x11.5mm.







PRODUCT OVERVIEW

Product name	Inverto Pendant NW Eb White
Technology	LED
Housing	Aluminium
Mount	Pendant surface
Environment	Internal
General application	Hospitality
ETIM Class	EC001743
Fixture luminous flux (lm)	1617 / 2045
Luminaire efficacy (lm/W)	102
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	40
Photobiological Risk Group	RG1
Total power consumption (W)	16
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK07
Product EAN number	8711971700500

PHOTOMETRY

Inverto Pendant Inverto Pendant NW Eb White 3070050



TECHNICAL DRAWINGS

