

ToLEDo Superia T5 ECG TOLEDO SUPĖRIA T5 HO 5FT 4200LM 840 0029514



Product features

- 60,000 hours average rated lifetime (L70 F50).
- Last 3 times longer than 49W 1449mm fluorescent tri-phosphor T5 lamp.
- High switching cycles 200,000X.
- High lumen efficacy -162lm/W.
- Omni-directional light distribution and wide beam angle.
- Minimum and maximum operating temperature: -20°C to 50°C.
- Glass construction and polycarbonate end-caps.
- Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast.
- Works only with compatible electronic ballasts.
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices.









PRODUCT OVERVIEW

Product name	TOLEDO SUPERIA T5 HO 5FT 4200LM 840
Technology	LED
Watt (Rated) (W)	26
General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries
ETIM Class	EC001959
E-number FI	4740611
E-number SE	8293584
Warranty	5 years
Luminous flux (lm)	4200
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam Angle (°)	220
Wattage (W)	26
Product Voltage (V)	80
Dimmable	No
Average life (Nominal) (h)	60000
Product EAN number	5410288295145