
Concord





Light the moment





Beacon XL Muse is a new addition to the innovative and award winning Beacon Muse range of spotlights. The soft-touch ring enables the end-user to manually adjust the beam from a wide flood (70°) down to a tight spot (10°); without the need of any additional lenses or reflectors.

Beacon XL Muse boasts a super high CRI of 97 with the R9 value at 90 -ensuring vibrant reds - the ideal spotlight for museum, gallery and retail applications where a high quality of light is required. Available with on-board dimming potentiometer, DALI or Sylsmart Wireless SSC dimming.

Concord Beacon XL Muse

















Features

- Unique adjustablity using soft-touch ring, enables beam control from a 10° spot to a 70° flood
 - 3000K 4000K
- Flood 70 deg 2544lm 2884lm
- 820lm 901lm • Spot 10 deg
- Ideal for museum, gallery and retail applications
- Super high colour rendering index, Ra 97 typical
- Available in 3000K or 4000K colourtemperatures
- On-board dimming, DALI or Casambi Bluetooth versions available
- For mounting on 3-circuit track (Lytespan 3)
- White or Black paint finishes as standard. Other colour available on request.
- Barn doors, Elongation lens, Honeycomb and Snoot accessories available
- IR/UV free light source without heat
- Long lifetime: 50,000 hours life at 70% of the original output (L70)

Product information

| Code | Description | Finish | Fixture Power (W) | Luminous Flux (lm) | Efficacy (lm/W) | Beam Angle (°) | Colour Temp (K) | CRI | Dimmable | Control Technology | Average Rated Life (Hrs) |
|----------|---------------------------------------|--------|-------------------------|--------------------------|--------------------|----------------------|-----------------------|-----|----------|-----------------------|--------------------------------|
| Beacon X | L Muse - 3000K (97CRI) | | | | | | | | | | |
| On-board | I DIM | | | | | | | | | | |
| 2059319 | Beacon XL Muse 3000K O/B DIM L3 White | White | 41 | 2544 | 62 | 10-70 | 3000 | 97 | Yes | Onboard Pot | 50,000 |
| 2059320 | Beacon XL Muse 3000K O/B DIM L3 Black | Black | 41 | 2544 | 62 | 10-70 | 3000 | 97 | Yes | Onboard Pot | 50,000 |
| DALI | | | | | | | | | | | |
| 2059323 | Beacon XL Muse 3000K DALI L3 White | White | 41 | 2544 | 62 | 10-70 | 3000 | 97 | Yes | DALI | 50,000 |
| 2059324 | Beacon XL Muse 3000K DALI L3 Black | Black | 41 | 2544 | 62 | 10-70 | 3000 | 97 | Yes | DALI | 50,000 |
| SylSmart | Wireless SSC | | | | | | | | | | |
| 2059327 | Beacon XL Muse 3000K SSC01 White | White | 41 | 2544 | 62 | 10-70 | 3000 | 97 | Yes | Sylsmart SSC | 50,000 |
| 2059328 | Beacon XL Muse 3000K SSC01 L3 Black | Black | 41 | 2544 | 62 | 10-70 | 3000 | 97 | Yes | Sylsmart SSC | 50,000 |
| Beacon X | L Muse - 4000K (IRC 97) | | | | | | | | | | |
| On-board | I DIM | | | | | | | | | | |
| 2059321 | Beacon XL Muse 4000K O/B DIM L3 White | White | 41 | 2884 | 70 | 10-70 | 4000 | 97 | Yes | Onboard Pot | 50,000 |
| 2059322 | Beacon XL Muse 4000K O/B DIM L3 Black | Black | 41 | 2884 | 70 | 10-70 | 4000 | 97 | Yes | Onboard Pot | 50,000 |
| DALI | | | | | | | | | | | |
| 2059325 | Beacon XL Muse 4000K DALI L3 White | White | 41 | 2884 | 70 | 10-70 | 4000 | 97 | Yes | DALI | 50,000 |
| 2059326 | Beacon XL Muse 4000K DALI L3 Black | Black | 41 | 2884 | 70 | 10-70 | 4000 | 97 | Yes | DALI | 50,000 |
| SylSmart | Wireless SSC | | | | | | | | | | |
| 2059329 | Beacon XL Muse 4000K SSC01 L3 White | White | 41 | 2884 | 70 | 10-70 | 4000 | 97 | Yes | Sylsmart SSC | 50,000 |
| 2059330 | Beacon XL Muse 4000K SSC01 L3 Black | Black | 41 | 2884 | 70 | 10-70 | 4000 | 97 | Yes | Sylsmart SSC | 50,000 |
| | | | | | | | | | | | |

Legend: O/B = On board dimming; DALI = DALI Dimmable; L3 = Lytespan 3; SSC01= SylSmart Standalone.

Additional Images











Beacon XL Muse - adjustable beam from 10° spot to 70° flood

Photometric Data





3000K Flood

4000K Spot



Dimensions (mm)






Concord Beacon XL Muse


Accessories

| Code | Description | | | | | | |
|-------------|---------------------------------|--|--|--|--|--|--|
| | | | | | | | |
| Accessories | | | | | | | |
| 2093113 | Beacon XL Muse Elongation | | | | | | |
| 2093114 | Beacon XL Muse Honeycomb | | | | | | |
| 2058328 | Beacon XL/XL Muse/XXL Barn Door | | | | | | |
| 2058326 | Beacon XL/XXL Snoot | | | | | | |
| 3020010 | Monopoint L3 White | | | | | | |
| 3020080 | Monopoint L3 Black | | | | | | |
| | | | | | | | |




Elongation lens






























Monopoint white

Monopoint black


Sylsmart SSC

- Wireless dimming of single or multiple luminaires with simple touch gestures on your smart phone
- Automatically form a wireless mesh network with the other Sylsmart Wireless SSC luminaires
- Set up simple or complex scenarios with single or multiple luminaires in them. All the luminaires in one scene can have different light levels according to the needs of the end-user
- Define the security of the network. There are four different security levels for access control
- Control luminaires visually, by adding photographs into the app to virtually recreate the room
- The Sylsmart Wireless SSC use Bluetooth Low Energy to form the direct connection and interaction between a mobile device and the luminaires
- Free app is available to download on iPhone and Android devices





Concord













Although every effort has been made to ensure accuracy in the compilation of the technical detail within this publication, specifications and performance data are constantly changing. Current details should therefore be checked with Feilo Sylvania International Group Kft. Copyright Feilo Sylvania International Group Kft. August 2020.

sylvania-lighting.com

A Feilo Sylvania Company