

DeltaWing LED - DALI dimmable & Microwave sensor

DELTAWING LED72 DALI MW 4K 1200
0044899



Product features

- Low profile surface and suspended LED diffuser luminaire, 1218mm x 200mm, 4000K Neutral White, DALI dimmable, Microwave sensor, 7260lm, 71W, lifespan: 55,000 hours L90B10, A++ A+ A



PRODUCT OVERVIEW

Product name	DELTAWING LED72 DALI MW 4K 1200
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting, Suspended
Environment	Internal
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC002892
Warranty	5 years
Fixture luminous flux (lm)	7260
Luminaire efficacy (lm/W)	102.25
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Beam Angle (°)	102
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	71
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	95
Housing colour	White
IP rating	IP44
IK rating	IK08
Product EAN number	5410288448992


PHOTOMETRY

DeltaWing LED - DALI dimmable & Microwave sensor DELTAWING LED72 DALI MW 4K 1200 0044899

0.5	1.24	E:0°	805
	1.64	E:C90	1021
1.0	2.48	E:0°	2010
	3.28	E:C90	2562
1.5	3.72	E:0°	267
	4.91	E:C90	335
2.0	4.96	E:0°	64
	6.55	E:C90	81
2.5	6.20	E:0°	21
	8.19	E:C90	27
3.0	7.44	E:0°	10
	9.83	E:C90	13

Distance [m] Core diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 113.2°)
 — C90 - C270 (Half beam angle: 102.2°)



TECHNICAL DRAWINGS

