

Skyline Street - Extra Large

Skyline Street XL 17-30klm NW MR20 I 9022
0066753



Product features

- The Skyline Street family is dedicated for road lighting applications. Light distribution: MR20 - Medium Road, color temperature: 4000K, total system power: 244W, total fixture output: 30009lm, luminaire efficacy: 123lm/W, LOR: 100%, colour rendering index: 70, LED Chromaticity: 5 step MacAdam ellipse tolerance, lifetime: 100000 hours at L90B50 @ 50°C, energy class: A++, A+, A, operating voltage: 220-240V / 50-60Hz, electronic driver, Without Controls, power factor: min. 0.9, electrical protection: Class I, Ingress protection rating: IP66, Impact resistance: IK08, dimensions: 915 x 415 x 140mm, weight: 15 kg, for 42-60mm side entry or post top installation with +/-15° adjustability, the housing is made of Die Cast Aluminium in RAL9022 color combined with tempered flat glass cover.



PRODUCT OVERVIEW

Product name	Skyline Street XL 17-30klm NW MR20 I 9022
Technology	LED
Housing	Aluminium
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC000062
Warranty	5 years
Fixture luminous flux (lm)	30009
Luminaire efficacy (lm/W)	123
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	70
Photobiological Risk Group	RG1
Total power consumption (W)	244
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	No
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288667539

DATA TABLE

General data

Product name	Skyline Street XL 17-30klm NW MR20 I 9022
Technology	LED
Housing	Aluminium
General application	Education, Hospitality, Logistics & Industry, Office, Retail
Operating temperature range (°C)	-40°C - 50°C

Skyline Street - Extra Large

Skyline Street XL 17-30klm NW MR20 I 9022
0066753

Performance ambient temperature Tq (°C)	25
ETIM Class	EC000062
Warranty	5 years

Optical data

Fixture luminous flux (lm)	30009
Luminaire efficacy (lm/W)	123
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	70
Distribution type	Road lighting
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	244
Mains voltage (V)	220-240V~
Lamp power factor	0.98
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	No
Drive current (mA)	760
Inrush Current (A)	65
Inrush Duration (µs)	268
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	5
Max. Luminaires per 13A C Breaker	7
Max. Luminaires per 16A C Breaker	8
Max. Luminaires per 20A C Breaker	10
Max. Luminaires per 10A B Breaker	3
Max. Luminaires per 13A B Breaker	4
Max. Luminaires per 16A B Breaker	5
Max. Luminaires per 20A B Breaker	6
Mains surge immunity (differential mode - > L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	10

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B50	100000
Lifespan L90 B50	100000

Skyline Street - Extra Large

Skyline Street XL 17-30klm NW MR20 I 9022
0066753

Physical data

Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	Glass
Nominal Product Length (mm)	915
Nominal Product Width (mm)	415
Nominal Product Height (mm)	140
Weight (kg)	15.0


Packaging

Single packaging type	Carton
Product EAN number	5410288667539
Packaging single length / height (cm)	96.0
Packaging single width (cm)	48.0
Packaging single depth (cm)	18.0
DUN14 (outer)	05410288667539
Units per outer package	1
Packaging outer length / height (cm)	96.0
Packaging outer width (cm)	48.0
Packaging outer depth (cm)	18.0

Safety data

Optimal operating condition (°C)	-40-50
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

Skyline Street - Extra Large

Skyline Street XL 17-30klm NW MR20 I 9022
0066753

