

Skyline Street - Extra Large

Skyline Street XL 17-30klm NW MR20 I 9022
0066753



Product features

- The Skyline Street family is dedicated for road lighting applications. Light distribution: MR20 - Medium Road, color temperature: 4000K, total system power: 244W, total fixture output: 30009lm, luminaire efficacy: 123lm/W, LOR: 100%, colour rendering index: 70, LED Chromaticity: 5 step MacAdam ellipse tolerance, lifetime: 100000 hours at L90B50 @ 50°C, energy class: A++, A+, A, operating voltage: 220-240V / 50-60Hz, electronic driver, Without Controls, power factor: min. 0.9, electrical protection: Class I, Ingress protection rating: IP66, Impact resistance: IK08, dimensions: 915 x 415 x 140mm, weight: 15 kg, for 42-60mm side entry or post top installation with +/-15° adjustability, the housing is made of Die Cast Aluminium in RAL9022 color combined with tempered flat glass cover.




PRODUCT OVERVIEW

Product name	Skyline Street XL 17-30klm NW MR20 I 9022
Technology	LED
Housing	Aluminium
General application	Education, Hospitality, Logistics & Industry, Office, Retail
ETIM Class	EC000062
Warranty	5 years
Fixture luminous flux (lm)	30009
Luminaire efficacy (lm/W)	123
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	70
Photobiological Risk Group	RG1
Total power consumption (W)	244
Electrical protection	Class I
Control gear type	Electronic ballast
Control gear mounting	Integral
Dimmable	No
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288667539

PHOTOMETRY

Skyline Street - Extra Large

Skyline Street XL 17-30klm NW MR20 I 9022
0066753



TECHNICAL DRAWINGS

