

## START eco Batten IP65 - NEW

START eco Batten 1500 IP65 3300lm 840  
0045752



### Product features

- The new upgraded START eco Batten IP65 is a versatile range of slimline LED waterproof luminaires that provide an ideal solution for applications such as workshops, garages and outdoor covered spaces. The design allows the luminaire to be easily linked to another luminaire through an IP65 rated connector. The product can be a slimline replacement for single and twin 36W/58W fluorescent waterproof battens. Polycarbonate housing and diffuser, 3300 lm, 23 W, 143 lm/W, 4000 K, drive current 320 mA, non dimmable, CRI 80, IP65, IK08, Class II, nominal average lifetime (h): 30000, 1570 mm x 43 mm x 50 mm, energy class: A++ A+ A.



### PRODUCT OVERVIEW

Product name	START eco Batten 1500 IP65 3300lm 840
Technology	LED
Housing	PC Polycarbonate
General application	Residential & Consumer
ETIM Class	EC000109
E-number FI	4278237
Warranty	3 years
Fixture luminous flux (lm)	3300
Luminaire efficacy (lm/W)	143
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	23
Electrical protection	Class II
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP65
IK rating	IK08
Product EAN number	5410288457529

### DATA TABLE

#### General data

Product name	START eco Batten 1500 IP65 3300lm 840
Technology	LED
Housing	PC Polycarbonate
General application	Residential & Consumer
Operating temperature range (°C)	-10°C - 40°C

## START eco Batten IP65 - NEW

*START eco Batten 1500 IP65 3300lm 840*  
0045752

Performance ambient temperature Tq (°C)	25
ETIM Class	EC000109
E-number FI	4278237
Warranty	3 years

### Optical data

Fixture luminous flux (lm)	3300
Luminaire efficacy (lm/W)	143
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Photobiological Risk Group	RG0

### Electrical data

Total power consumption (W)	23
Mains voltage (V)	220-240V~
Lamp power factor	0.9
Electrical protection	Class II
No. Of switching cycles before premature failures	>100000
Dimmable	No
Drive current (mA)	320
Inrush Current (A)	50
Inrush Duration (µs)	500
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	48
Max. Luminaires per 13A C Breaker	62
Max. Luminaires per 16A C Breaker	75
Max. Luminaires per 20A C Breaker	96
Max. Luminaires per 10A B Breaker	28
Max. Luminaires per 13A B Breaker	36
Max. Luminaires per 16A B Breaker	44
Max. Luminaires per 20A B Breaker	56

### Lifetime data

Lifespan L70 B50	50000
Lifespan L80 B50	30000

### Physical data

Housing colour	White
IP rating	IP65
IK rating	IK08
Diffuser finish	Opal

## START eco Batten IP65 - NEW

START eco Batten 1500 IP65 3300lm 840  
0045752

Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1570
Nominal Product Width (mm)	43
Nominal Product Height (mm)	50
Weight (kg)	0.6

### Packaging

Single packaging type	Carton
Product EAN number	5410288457529
Packaging single length / height (cm)	159.6
Packaging single width (cm)	4.6
Packaging single depth (cm)	5.3
DUN14 (outer)	15410288457526
Units per outer package	15
Packaging outer length / height (cm)	164.0
Packaging outer width (cm)	25.0
Packaging outer depth (cm)	18.0

### Safety data


Optimal operating condition (°C)	-10-40
----------------------------------	--------

## PHOTOMETRY

Distance [m]	Cone diameter [m]	E(0°)	E(C90)	E(C90)	3400
0.5	1.30 3.91	82.5°	74.1°	384	35
1.0	2.61 7.02	82.5°	74.1°	96	9
1.5	3.91 10.53	82.5°	74.1°	40	4
2.0	5.21 14.04	82.5°	74.1°	24	2
2.5	6.52 17.55	82.5°	74.1°	16	1
3.0	7.82 21.06	82.5°	74.1°	11	1

Distance [m]      Cone diameter [m]      Illuminance [lx]

— C0 - C180 (Half beam angle: 148.2°)  
— C90 - C270 (Half beam angle: 105.0°)



## TECHNICAL DRAWINGS

