

ToLEDo Superia T5 ECG

TOLEDO SUPERIA T5 HE 4FT 2400LM 840
0029505



Product features

- 60,000 hours average rated lifetime (L70 F50).
- Last 3 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp.
- High switching cycles - 200,000X.
- High lumen efficacy -150lm/W.
- Omni-directional light distribution and wide beam angle.
- Minimum and maximum operating temperature: -20°C to 50°C.
- Glass construction and polycarbonate end-caps.
- Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast.
- Works only with compatible electronic ballasts.
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



PRODUCT OVERVIEW

| | |
|----------------------------|---|
| Product name | TOLEDO SUPERIA T5 HE 4FT 2400LM 840 |
| Technology | LED |
| Watt (Rated) (W) | 16 |
| General application | Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries |
| ETIM Class | EC001959 |
| E-number FI | 4740602 |
| E-number SE | 8293575 |
| Warranty | 5 years |
| Luminous flux (lm) | 2400 |
| Colour temperature (K) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Beam Angle (°) | 220 |
| Wattage (W) | 16 |
| Product Voltage (V) | 80 |
| Dimmable | No |
| Average life (Nominal) (h) | 60000 |
| Product EAN number | 5410288295053 |