

Sylproof Tubular LED - DALI

Sylproof Tubular LED 1X600 DALI WW
0047604



Product features

- Aesthetically attractive and highly efficient LED tubular luminaire, opaque acrylic diffuser, stainless steel end caps and mounting brackets, rapid connector, as Sylvania Sylproof Tubular LED




PRODUCT OVERVIEW

Product name	Sylproof Tubular LED 1X600 DALI WW
Technology	LED
Cap/Base	N/A
Housing	Acrylic PMMA
Mount	Ceiling surface mounting
Environment	Interior
General application	Logistics & Industry
ETIM Class	EC000109
Warranty	5 years
Fixture luminous flux (lm)	1287
Luminous flux (lm)	1287
Luminaire efficacy (lm/W)	99
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	RG0
Total power consumption (W)	13
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	Yes
Minimum dimming level (%)	90
Housing colour	Transparent
IP rating	IP66
IK rating	IK06
Product EAN number	5410288476049

PHOTOMETRY

Sylproof Tubular LED - DALI Sylproof Tubular LED 1X600 DALI WW 0047604



Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [ft]	Illuminance [lx]
0.5	1.14	5.0'	160"	1607
	1.78	5.0'	48.7"	231
1.0	2.28	5.0'	56	622
	3.56	5.0'	48.7"	24
1.5	3.41	5.0'	179	179
	5.15	5.0'	25	25
2.0	4.55	5.0'	14	14
	7.13	5.0'	6	6
2.5	5.69	5.0'	9	9
	8.54	5.0'	4	4
3.0	6.83	5.0'	6	6
	10.69	5.0'	3	3

Distance [m] Cone diameter [m] Illuminance [lx]
 — C0 - C180 (Half beam angle: 151.4°)
 — C90 - C270 (Half beam angle: 97.4°)

TECHNICAL DRAWINGS

