

Skyline Street - Small

Skyline Street S 1-5klm NW NR14 I 9022

0066627



Product features

- The Skyline Street family is dedicated for road lighting applications. Light distribution: NR14 - Narrow Road, color temperature: 4000K, total system power: 49W, total fixture output: 6030lm, luminaire efficacy: 123lm/W, LOR: 100%, colour rendering index: 70, LED Chromaticity: 5 step MacAdam ellipse tolerance, lifetime: 100000 hours at L90B50 @ 50°C, energy class: A++, A+, A, operating voltage: 220-240V / 50-60Hz, electronic driver, Without Controls, power factor: min. 0.9, electrical protection: Class I, Ingress protection rating: IP66, Impact resistance: IK08, dimensions: 525x255x105mm, weight: 6 kg, for 42-60mm side entry or post top installation with +/-15° adjustability, the housing is made of Die Cast Aluminium in RAL9022 color combined with tempered flat glass cover.



PRODUCT OVERVIEW


Product name	Skyline Street S 1-5klm NW NR14 I 9022
Technology	LED
Housing	Aluminium
Mount	Post top
General application	Office, Hospitality, Retail, Logistics & Industry, Education
ETIM Class	EC000062
Warranty	5 years
Fixture luminous flux (lm)	6030
Luminaire efficacy (lm/W)	123
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	70
Photobiological Risk Group	RG1
Total power consumption (W)	49
Electrical protection	Class I
Control gear type	Electronic ballast
Dimmable	No
Housing colour	RAL 9022 - Pearl light grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288666273

PHOTOMETRY

Skyline Street - Small

Skyline Street S 1-5klm NW NR14 I 9022

0066627



TECHNICAL DRAWINGS

